SP SERIES

1000-1500-2000 VA

code name **SPIDY**

SP Series uninterruptible power supply prevents data loss and saves devices in case of power outage

Spidy at 1000, 1500 and 2000 VA power provides economical and safe protection with its storable pretty design.

Uninterruptable Power Supply & Data Center Infrastructure Solutions

www.necron.com.tr/en | info@necron.com.tr

Technical specifications

	SP SERIES	SP1000VA	SP1500VA	SP2000VA
INPUT	Power	1000VA / 600W	1500VA / 900W	2000VA / 1200W
	Voltage Tolerance	1 Phase + Neutral		
	Voltage	220 VAC ± %25		
	Frequency	50 Hz ± %10		
OUTPUT	Voltage	220 VAC ± %10		
	Voltage Wavefrom	Pure Sine Wave (mains); Pure Sine Wave (battery mode)		
	Frequency	50 Hz ± %1 (battery mode)		
	Crest Factor	3:1		
	Transfer Time	< 10ms		
	Socket Type		3 x Grounding Plug	
BATTERY	Model	VRLA		
	Battery	2 x 12V / 7Ah	2 x 12V / 9Ah	
	Charging Time	For 90% Capacity 8 Hours		
	Back-Up Time	10-20 Minutes, Load Depends On the Level of		
GENERAL	Modem and Network Protection	Modem / LAN - RJ11 / RJ45		
	Communication	USB		
	Noise Level (1m)	< 42dBA		
	Temperature	0 ~ 40 °C		
	Humidity	20 ~ 90% (non-condensed)		
	Weight	10.1 kg	13.5 kg	
	Dimension (WxHxD)	125x220x400 mm	125x220x400 mm	